



Electrical Characteristics							@25°C
Switch available for this series	—	1	2	3	4	5	
Contact form	—	A	A	A	B	C	
Contact rating max.	W/VA	10	—	—	—	—	
Switching voltage max.	VDC VAC	100 100	—	—	—	—	
Switching current max.	A	0.5	—	—	—	—	
Carry current	A	0.5	—	—	—	—	
Breakdown voltage min.	VDC	180	—	—	—	—	
Total resistance max. (initial)	mΩ	150	—	—	—	—	
Magnetical Characteristics (of unmodified Reed Switch)							@25°C
Switch	—	1	2	3	4	5	
Pull in (available range)	AT	10-35	—	—	—	—	
Drop out min.	AT	3	—	—	—	—	
Environmental Characteristics							
Operating temperature	°C	-20...+80	—	—	—	—	
Material Information							
Switch	—	1	2	3	4	5	
Housing material	—	PA66GF	—	—	—	—	
Housing color	—	blue	—	—	—	—	
Cable type	—	UL1061	—	—	—	—	
Cable AWG	—	26	—	—	—	—	
Cable color	—	red	—	—	—	—	
Available Magnet	Customized version (available upon request)				Approvals		
MMA-202	AT value / Cable type / Cable AWG / Cable color / Cable length / Cable ends / Housing color / Connector assembly				RoHS,REACH		