



**Electrical Characteristics** @25°C

		1	2	3	4	5
Switch available for this series	—	1	2	3	4	5
Contact form	—	A	A	A	B	C
Contact rating max.	W/VA	1	—	—	—	—
Switching voltage max.	VDC VAC	24 24	—	—	—	—
Switching current max.	A	0.1	—	—	—	—
Carry current	A	0.3	—	—	—	—
Breakdown voltage min.	VDC	150	—	—	—	—
Total resistance max. (initial)	mΩ	200	—	—	—	—

**Magnetical Characteristics (of unmodified Reed Switch)** @25°C

		1	2	3	4	5
Switch	—	1	2	3	4	5
Pull in (available range)	AT	10-25	—	—	—	—
Drop out min.	AT	5	—	—	—	—

**Environmental Characteristics**

		-20...+80	—	—	—	—
Operating temperature	°C	-20...+80	—	—	—	—

**Material Information**

		1	2	3	4	5
Switch	—	1	2	3	4	5
Housing material	—	PA66GF	—	—	—	—
Housing color	—	blue	—	—	—	—
Cable type	—	UL1061	—	—	—	—
Cable AWG	—	26	—	—	—	—
Cable color	—	red	—	—	—	—

Available Magnet	Customized version (available upon request)	Approvals
MMA-203	AT value / Cable type / Cable AWG / Cable color / Cable length / Cable ends / Housing color / Connector assembly	RoHS,REACH